

**Clusters**

- Sandbox
- Permissions
- Go to Dashboard
- Versions

**Views**

- Views

**User + Group Management**

- Users
- Groups

## Views / Hive View Go to instance (/#/main/views/HIVE/1.0.0/AUTO\_HIVE\_INSTANCE)

Delete Instance

**View** **HIVE**

**Version**

**Details**  Edit ()

**Instance Name**

**Display Name**

**Description**

Visible

**Permissions**

Permission	Grant permission to these users	Grant permission to these groups
Use	<input type="text" value="hive_user1 ()"/> <input type="text" value="hive_user2 ()"/>	<input type="text" value="Add Group"/>

**Settings**  Edit ()

Hive Authentication

WebHDFS Username

WebHDFS Authentication

Instance name of Tez view

**Scripts HDFS Directory\***

**Jobs HDFS Directory\***

**Default script settings file\***

**Cluster Configuration** ✎ Edit ()

Local Ambari Managed Cluster

Cluster Name

Custom

**HiveServer2 Host\***

**HiveServer2 Thrift port\***

**HiveServer2 Http port\***

**HiveServer2 Http path\***

**HiveServer2 Transport Mode\***

**WebHDFS FileSystem URI\***

Logical name of the NameNode cluster

List of NameNodes

First NameNode RPC Address

Second NameNode RPC Address

First NameNode HTTP (WebHDFS) Address

Second NameNode HTTP (WebHDFS) Address

Failover Proxy Provider

Auth To Local

**YARN Application Timeline Server URL\***

**YARN ResourceManager URL\***